



High Speed Data Line Protector – HSP10K36 (700805)



- Multi-stage protection with primary or combination primary/secondary protectors
- 10 pair protector
- Provides both L-L and L-PE protection modes for comprehensive protection
- Simple installation into Krone® LSA disconnect block
- Data Line Terminator (DLT) available where screw terminal connections are required



Part Number	HSP10K36
Article Number	700805
Max Continuous Operating Voltage (Uc)	40 VDC
Max Discharge Current (Imax), L+L-PE	20 kA 8/20 μ s
Rated Load Current (IL)	150 mA
Frequency	12 MHz Max
Transmission Rate	8 Mb/s
Protection Modes	L-L L-PE
Technology	Multi-stage
Connection Type	Krone® LSA-PLUS
Impedance Balance	55 dB Max
Insertion Loss	.4 Db Max
Return Loss	20 dB Max
Loop Resistance	16.4 Ω
Temperature	-20 to 60 °C
Enclosure Material	UL® 94V-0 thermoplastic
Depth (D)	21 mm
Height (H)	35 mm
Width (W)	125 mm
Unit Weight	0.02 kg
Certifications	CE C-Tick cULus



Part Number	HSP10K36
Standard Packaging Quantity	1 pc
UPC	78285647506
EAN-13	8711893024678

Krone is a registered trademark of ADC GMBH. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

