

Square Tape Clamps

These Wallis four-way connectors are suitable for making cross, straight through or tee joints in flat tape. The base has a countersunk hole in the middle for securing the clamp to the building surface and the lid is fixed by means of four screws.

Fix using countersunk woodscrew 1 1/2" x No. 10 and No. 10 wall plug.

For use with Bare Copper Tapes

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	50	50	13	0.15	25	JG 253
25 x 6	50	50	20	0.25	25	JG 256
31 x 3	60	60	14	0.22	25	JG 313
38 x 6	71	71	22	0.59	25	JG 386
50 x 3	80	80	16	0.50	10	JG 503
50 x 6	79	79	22	0.52	10	JG 506

Material: Gunmetal.

For use with Lead Covered Copper Tape

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	70	70	25	0.86	25	JPB 253 L

Material: Phosphor Bronze.

For use with Bare Aluminium Tape

Conductor Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
25 x 3	50	50	13	0.07	25	JA 253

Material: Aluminium.



BS EN 62561-1 Class H



Tightening torque 6 Nm

