

CONNETTORI A "C"

"C" CONNECTORS



MATERIALE: Rame elettrolitico 99,9

MATERIAL: 99,9 electrolytic copper

CE



ARTICOLO	SEZIONE	PASSANTE	DERIVATO	A	B	PEZZI PER CONFEZIONI
PART	WIRE RANGE mm ²	WIRE RANGE mm ²	WIRE RANGE mm ²			PIECES PER BOX
GC 1	6-6	6-2,5	6-1,5	9	10	100/500
GC 2	10-10	10	10-1,5	12	12	100/250
GC 3	16-16	16	16-1,5*	17	19,5	100
GC 4	25-16	25-16	10-1,5*	17	19	100
GC 5	25-25	25	25-16	17	20,5	100
GC 6	35-16	35	16-6*	20,5	24	50
GC 7	35-35	35	35-25	20,5	26,5	50
GC 8	70-35	70-50	35-6*	26	28	25
GC 9	70-50	70-50	70-50	24	31	25
GC 10	95-35	95	35-6*	29	40,5	25
GC 11	95-70	95	70-35	27	40,5	25
GC 12	95-95	95	95	29	41	20
GC 13	120-120	120	120-25	30	45	10
GC 14	150	150	150-120	31	45,5	10
GC 15	185-95	185-150	95-16	31	44,4	10
GC 16	240-120	240-150	120-95	22,6	68	10

*Dove c'è l'asterico si consiglia di raddoppiare il conduttore.

Pinza idraulica manuale Art. 55	Art.	Sezione mm ²
Matrici	M2/55	6
	M2/55	10
	M2/55	16-25
	M2/55	35
	M2/55	50-70

Pinza consigliata Art. 58 Idraulica manuale	Art.	Sezione mm ²
Matrici	M2/58	6-10
	M2/58	16-25
	M2/58	35
	M2/58	50-70
	M2/58	95
	M2/58	120-185

Pinza idraulica pedale Art. 59	Art.	Sezione mm ²
Matrici	M2/59	16-25
	M2/59	35
	M2/59	50-70
	M2/59	95-120

Art. 58	Art.	M2/58610	M2/581625	M2/5835	M2/585070	M2/5895	M2/58120185
Art. 55	Art.	M2/55-6	M2/55-10	M2/55-16-25		M2/55-35	M2/55-50-70