

Earth terminal blocks

- mounted onto PR/3 profiles conforming to IEC 60715 standards, TH/35 and "G32" type
- in a single yellow/green shell
- certificate **CESI 02 ATEX 061 U EX e** Ex II M2 / II 2 G D temperature range of use: -40 – +80°C
- **CoC IEC Ex CES 09.0010U** Ex e II
- maximum continual operating temperature 100°C



(*) with reference to upper and lower clamping units respectively

version to be mounted onto PR/3 rail	TEO.2	Cat. No.	T0910	CBE.2	Cat. No.	CE110	TEO.4	Cat. No.	T0430
TECHNICAL CHARACTERISTICS									
function/type	earth			earth (2 inputs / 2 outputs)			earth		
rated cross-section (mm ²)	2.5			2.5			4		
connecting capacity									
flexible (mm ²)	0.2 – 4			0.2 – 4			0.2 – 6		
rigid (mm ²)	0.2 – 4			0.2 – 4			0.2 – 6		
max. flexible with ferrule (mm ²) - ferrule type	2.5 - WP25/14			2.5 - WP25/14			4 - WP40/16		
rated voltage / rated current / gauge conf. to IEC 60947-7-1	- / - / A3			- / - / A3			- / - / A4		
rated voltage / rated current / AWG / tightening torque value UL (Ex e) rated voltage (V)	- / - / 20-14 AWG / 5.5 lb.in.			- / 15 A / 20 – 14 AWG / 5.5 lb.in.			- / - / 20 – 12 AWG / 5.5 lb.in.		
rated impulse withstand voltage / pollution degree	8 KV / 3			8 KV / 3			8 KV / 3		
insulation stripping length (mm)	12			8 - 14.5 (*)			14		
tightening torque value (test / max) (Nm)	0.4 / 0.8			0.4 / 0.5			0.5 / 1.2		
height / width / thickness TH/35 7.5 mm	47 / 50 / 5.5			52 / 50 / 5			52 / 50 / 6.5		
height / width / thickness TH/35 15 mm	55 / 50 / 5.5			60 / 50 / 5			60 / 50 / 6.5		
height / width / thickness G32	-			56 / 50 / 5			-		
APPROVALS									
ACCESSORIES	Type	Cat. No.	Type	Cat. No.	Type	Cat. No.	Type	Cat. No.	
End section	TEO.2/PT	T0911	CBR/PT	CR111	TEO.4/PT	T0431	CBR/PT	CR111	
Marking tag	CNU/8/51	NU0851	CNU/8/51	NU0851	CNU/8/51	NU0851	CNU/8/51	NU0851	
Numbering strip	-	-	-	-	-	-	-	-	
End bracket	BTU for PR/DIN and PR/3	BT005	BTU for PR/DIN and PR/3	BT005	BTU for PR/DIN and PR/3	BT005	BTU for PR/DIN and PR/3	BT005	
	BT/3-BTO for PR/3 only	BT003-BT007	BT/3-BTO for PR/3 only	BT003-BT007	BT/3-BTO for PR/3 only	BT003-BT007	BT/3-BTO for PR/3 only	BT003-BT007	
	BT/DIN/PO for PR/DIN only	BT001							

MAXIMUM SHORT-TIME WITHSTAND CURRENTS ALLOCATED TO THE RAIL PROFILE				
Rail profile	Material	Equivalent E-cu cross-section mm ²	Short-time withstand current 1 s kA	Thermal rated current of a PEN busbar A
"Top hat" rail IEC 60715/TH 15 - 5.5	Steel Copper Aluminium	10 25 16	1.2 3 1.92	- 101 76
"Top hat" rail IEC 60715/TH 35 - 7.5	Steel Copper Aluminium	16 50 35	1.92 6 4.2	- 150 125
"Top hat" rail IEC 60715/TH 35 - 15	Steel Copper Aluminium	50 150 95	6 18 11.4	- 309 232