



pluso

plugs and socket-outlets
for industrial purposes
low voltage

- in compliance with EN 60309-1 and -2 standards
- body, inserts and locknut made of insulating, thermoplastic, self-extinguishing material
- PE...SV (IP44) types, entry with cable gland in operating voltage colour, RAL 7035 grey colour body

- PEW...SV (IP66/IP67) types, entry with cable gland in operating voltage colour, RAL 7035 grey colour body, locknut with gasket, in the operating voltage colour
- fixing captive screws
- with Italian Quality Mark

picture	ILME part No.	description	packaging
---------	---------------	-------------	-----------

plugs - splashproof IP44 (EN 60529) - Squich® connection

NEW



100÷130V ~ - 50 and 60 Hz - yellow			
PES 1643 SV	16A - 2P + ⊕	- 4h ●	10
PES 1644 SV	16A - 3P + ⊕	- 4h ●	10
PES 1645 SV	16A - 3P + N + ⊕	- 4h ●	10
200÷250V ~ - 50 and 60 Hz - blue			
PES 1663 SV	16A - 2P + ⊕	- 6h ● ◇	100
PES 1694 SV	16A - 3P + ⊕	- 9h ●	10
PES 1695 SV	16A - 3P + N + ⊕	- 9h ●	10
380÷415V ~ - 50 and 60 Hz - red			
PES 1693 SV	16A - 2P + ⊕	- 9h ●	10
PES 1664 SV	16A - 3P + ⊕	- 6h ● ◇	100
PES 1665 SV	16A - 3P + N + ⊕	- 6h ● ◇	50

plugs - watertight IP66/IP67 (EN 60529) - Squich® connection


NEW



100÷130V ~ - 50 and 60 Hz -yellow			
PESW 1643 SV	16A - 2P + ⊕	- 4h ●	10
PESW 1644 SV	16A - 3P + ⊕	- 4h ●	10
PESW 1645 SV	16A - 3P + N + ⊕	- 4h ●	10
200÷250V ~ - 50 and 60 Hz - blue			
PESW 1663 SV	16A - 2P + ⊕	- 6h ● ◇	40
PESW 1694 SV	16A - 3P + ⊕	- 9h ●	10
PESW 1695 SV	16A - 3P + N + ⊕	- 9h ●	10
380÷415V ~ - 50 and 60 Hz - red			
PESW 1693 SV	16A - 2P + ⊕	- 9h ●	10
PESW 1664 SV	16A - 3P + ⊕	- 6h ● ◇	20
PESW 1665 SV	16A - 3P + N + ⊕	- 6h ● ◇	20

◇ The articles with hour position 6h refer to the rated voltage (2P+⊕/220÷250V ~ - 3P+⊕ and 3P+N+⊕/380÷415V ~)
Other executions not listed but within the norm can be supplied on request
Loose protective cover (accessory for plugs): page 23

**SQUICH® CONNECTION
THE TIMESAVER**



**60% FASTER
CONNECTION TIME**

