



## pluso - PB

plugs and socket-outlets  
for industrial purposes  
extra low voltage

- in compliance with European standards EN 60309-1 and -2
- body, insert and spring lid in insulating thermoplastic self-extinguishing material
- wall-mounting types: top entry with threaded grommet (replaceable with cable gland)
- mobile plugs and couplers types: cable anchoring collar incorporated in the insert, entry with grommet

picture

ILME  
part No.

description

packaging

### wall-mounting sockets - splashproof IP44 (EN 60529)



#### 16A

<b>PB 16002 PP</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way - Pg 21	10
<b>PB 16003 PP</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way - Pg 21	10
<b>PB 16122 PP</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h - Pg 21	10
<b>PB 16123 PP</b>	3P - ○ 40÷50V ~ - 50 and 60 Hz - 12h - Pg 21	10
<b>PB 16042 PP</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h - Pg 21	10
<b>PB 16043 PP</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h - Pg 21	10
<b>PB 16112 PP</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h - Pg 21	10
<b>PB 16113 PP</b>	3P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h - Pg 21	10
<b>PB 16102 PP</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h - Pg 21	10

#### 32A

<b>PB 32002 PP</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way - Pg 21	10
<b>PB 32003 PP</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way - Pg 21	10
<b>PB 32122 PP</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h - Pg 21	10
<b>PB 32123 PP</b>	3P - ○ 40÷50V ~ - 50 and 60 Hz - 12h - Pg 21	10
<b>PB 32042 PP</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h - Pg 21	10
<b>PB 32043 PP</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h - Pg 21	10
<b>PB 32112 PP</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h - Pg 21	10
<b>PB 32113 PP</b>	3P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h - Pg 21	10
<b>PB 32102 PP</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h - Pg 21	10

### plugs - splashproof IP44 (EN 60529)



#### 16A

<b>PB 16002 SV</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way	20
<b>PB 16003 SV</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 16122 SV</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 16123 SV</b>	3P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 16042 SV</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 16043 SV</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 16112 SV</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 16113 SV</b>	3P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 16102 SV</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h	10

#### 32A

<b>PB 32002 SV</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 32003 SV</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 32122 SV</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 32123 SV</b>	3P - ● 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 32042 SV</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 32043 SV</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 32112 SV</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 32113 SV</b>	3P - ○ 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 32102 SV</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h	10

### couplers - splashproof IP44 (EN 60529)



#### 16A

<b>PB 16002 PV</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 16003 PV</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 16122 PV</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 16123 PV</b>	3P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 16042 PV</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 16043 PV</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 16112 PV</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 16113 PV</b>	3P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	1
<b>PB 16102 PV</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h	10

#### 32A

<b>PB 32002 PV</b>	2P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 32003 PV</b>	3P - ● 20÷25V ~ - 50 and 60 Hz - no key way	10
<b>PB 32122 PV</b>	2P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 32123 PV</b>	3P - ○ 40÷50V ~ - 50 and 60 Hz - 12h	10
<b>PB 32042 PV</b>	2P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 32043 PV</b>	3P - ● 20÷25V and 40÷50V ~ - 100÷200 Hz - 4h	10
<b>PB 32112 PV</b>	2P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	10
<b>PB 32113 PV</b>	3P - ● 20÷25V and 40÷50V ~ - 400÷500 Hz - 11h	1
<b>PB 32102 PV</b>	2P - ○ 20÷25V and 40÷50V ~ - 10h	10

16A and 32A versions with nickel-plated contacts can be supplied on request