

## Small pedestal

### Features

- Small outdoor enclosure with integrated base.
- Easy to install by one person only (weight: 4.5 kg).
  - Overall dimension 753x385x270 (HxWxD in mm).
  - Easy cover installation because of sliders and snap-on lock.
  - Base in high density polyethylene (HDPE) RAL 9005.
  - Base resists a ground temperature of -50°C.
  - The upper part of the base serves as a mounting plate (190x225mm - HxW) and is provided with three slots for fixation points.
  - Moulded-in indication of burial depth.
  - Cover in light-grey colour RAL 7035.
    - non-ventilated or ventilated version in hot-moulded, glass-fibre reinforced polyester.
    - cover locked by means of spring-lock mechanism.
    - cover to be opened by means of triangular key (8mm, accessory).
  - Degrees of protection:
    - IP23D for the non ventilated cover.
    - IP20 for the ventilated cover.
- According to EN/IEC 60529.
- Protection degree IK09 against external mechanical impacts according to EN/IEC 62262.

### Applications



- Cable television distribution (CATV)
- Telecommunication (surface terminal cabinet)
- Camping sites and garden installations
- Gas distribution

### Standards

EN/IEC 62208

### EH1 - Pedestal

Type	Ref. No.	Pack.
Ventilated	841037	1
Non-ventilated	841038	1
<b>Accessories</b>		
Triangular key (8mm) for cover-lock	832027	1
Ventilated spare cover	841039	1
Non-ventilated spare cover	841040	1
Retro-fit set (catch-plate and screw)	841041	1



Overview of the range ● Page C.2

Dimensional drawings ● Page I.32

Specifications for tender documents ● Page I.60

Power dissipation values ● Page I.84